

# 2" Polypropylene Hydraulic Centrifugal Pump Hydraulic Driven Poly Pump

## GRESEN MGG2 HYDRAULIC MOTOR

- Hydraulic fluid capacity Min. 6 gal./Max. 10 gal.
- 12 H.P. Motor.
- Open or closed system.
- 3600 R.P.M.



2" HYDRAULIC DRIVEN POLYPROPYLENE PUMP

## TECH DATA:

U.S. Gallons/Rev.	0.0025
Cubic Inches/Rev.	0.580
Liters/Rev.	0.0097

Max Hydraulic Pressure	2000 P.S.I.
Min Hydraulic Pressure	200 P.S.I.

Inlet Port SAE 10 (7/8-14 UNF-2B)  
Outlet Port SAE 10 (7/8-14 UNF-2B)

- Minimum Hydraulic GPM required to motor for Banjo Pump 6 GPM (2400 rpm)
- Maximum Hydraulic GPM required to motor for Banjo Pump 10 GPM (4000 rpm)
- Ideal GPM required to motor for Banjo Pump 13.7 GPM (3600 rpm)

## CONNECTION INFORMATION:

- Inlet ("A" port)
- Outlet ("B" port)
- Supplied check valve is to ensure proper rotation of the Banjo pump. Place check Valve in outlet port (marked "B") for proper right hand rotation.